

NANO 2

NEW GENERATION, MORE FEATURES
(PSTN & VOIP)



8 People Conference

32 IP and 16 TDM simultaneous calls

Upto 100 extensions

Fax and Voicemail to Email

DESIGNED &
MANUFACTURED IN INDIA

Compact, all-in-one telephone system that includes the rich features of a PBX

Easy to Install, Easy to use, Easy on the eye. The NANO2 was designed for the SMB, SOHO segment delivering all the advanced features of an Asterisk based PBX controlled by an clear and user friendly GUI. Not all PBX systems belong in a rack or mounted on a wall, reliable appliance that looks good.

Call Features

- Callback
- Call Recording
- BILLING interface
- FAX and VOICEMAIL to Email
- Directory Service
- Call Restriction
- 8 Ports (2FXO-4FXS-2 FXO/FXS)
- Music on Hold
- RTC (Real Time Clock & Date)
- Easy to use GUI
- 1 GB SD card for Music and Voicemail (can support up to 8GB)

Call Features

- Call Forwarding, Transfer, Waiting, Park, Pick-up, 3 way calling, Hunt group and more

Physical & Environment

Operating Temperature: 10°C to 40°C (50°F to 104°F)
 Operating humidity: 10% to 90%, Non-condensing
 Storage temperature: 0°C to 50°C (32°F to 122°F)
 Storage humidity: 5% to 95%, Non-condensing
 Unit Weight: 0.55 kg
 Dimensions: 175mm (W) x 253mm (L) x 34 mm(H)
 (6.88" x 9.96" x 1.33")
 Power Input: 12V DC / 2.5 A

System Capacity

- 2 FXO, 4 FXS, 2 FXO/FXS programmable
- 100 IP extensions, Up to 6 Analog extensions

Auto-Attendant Features

- Configurable IVR
- Queue creation
- Music on hold
- Scheduling for IVR with RTC (real time clock) supporting date/time

Messaging

- Up to 100 hours
- Each extension has access to Voice Mail
- Remote Voice Mail access

Technical Specification

Model Name: CPX-002
Ports: 2 10/100Mbps RJ-45 Network Port for WAN/LAN
 6 RJ-11 FXS Port for VoIP (programmable)
 4 RJ-11 FXO port for PSTN
LEDs: Power, Ethernet, Phones and Lines
Memory: 1 GB Secure Digital (SD) Card Slot
Voice Protocol: Session Initiation Protocol (SIP v2)
Voice Codec: G.711 A-law, G.711 μ-law, G.729AB, G.726, G.723.1
Ringer Equivalence: 3 REN per RJ-11 port
Ring Frequency: 30Hz
FXS Port Impedance: Pre-set Progress Tones for Multiple Regions including 600 / 900 ohms
Ring Voltage: 90 Vrms Configurable
Security: Password-protected management



For more information please contact

Canada: +1 778 892 2877 | andre@allo.com
 India: +91 80 67080808

NanoPBX Pricing Information

Number of Units	Price/unit/USD/FOB Bangalore, India
5 Units	\$345.00
10 Units	\$290.00
20 Units + OEM* possible	\$290.00
50 Units	\$275.00
100 Units	\$265.00
500 Units	\$250.00
1000 Units	\$245.00

Sample Unit Value **\$375**
(shipping included)

*OEM:

- Customized GUI
- Plain Product
- Plain Box

MSRP: **\$425 USD**

Contact Information

Andre Martin Strul
Marketing Manager

Phone:
+1-778-892-2877

Email:
wholesales@allo.com

